


# Common Mode Line Chokes

## High Inductance Series





These common mode line chokes provide the best available combination of low cost and high inductance. Coilcraft EE style common mode line chokes are available in two series, each with a variety of current ratings, sizes and inductance values. The Coilcraft bobbin design provides a creepage and clearance spacer that makes these parts compatible with UL, VDE, and IEC specifications.



Coilcraft **Designer's Kit No. P202** contains samples of 8 standard EE and toroidal common mode line chokes. To order, please contact Coilcraft.

- VDE, IEC, CSA compatible
- Cost effective design
- 3750 Vrms isolation between windings

### F55XX Series



### H70XX Series



*Coilcraft*

Document 142-1 Revised 7/9/97

# Common Mode Line Chokes—High Inductance Series

## F55XX Series

Part Number	Inductance (mH)	Current (Amps)	SRF (kHz)	R <sub>DC</sub> (Ohms)
F5585-A	82	1/2	65	.31
F5586-A	34	3/4	100	.13
F5587-A	24	1	129	.86
F5588-A	15	1 1/4	170	.54
F5589-A	7.5	1 1/2	206	.30
F5590-A	6.0	2	230	.22
F5591-A	3.3	2 1/2	309	.12
<b>F5592-A</b>	<b>1.6</b>	<b>3</b>	<b>420</b>	<b>.07</b>
<b>F5593-A</b>	<b>1.1</b>	<b>4</b>	<b>560</b>	<b>.04</b>

Parts in bold type are included in Coilcraft Designer's Kit No. P202.

## H70XX Series

Part Number	Inductance (mH)	Current (Amps)	SRF (kHz)	R <sub>DC</sub> (Ohms)
H7010-A	56	1	62	.11
H7011-A	34	1 1/4	96	.72
H7012-A	23	1 1/2	104	.47
H7013-A	20	2	128	.35
H7014-A	7.3	2 1/2	190	.16
H7015-A	5.3	3	220	.12
H7016-A	4.0	4	275	.08
H7017-A	2.0	5	370	.05
H7018-A	.95	6	556	.03
H7019-A	.75	8	640	.02

**Notes:** 1. Inductance is minimum per winding, tested at .1 Vrms, 20 kHz.  
 2. R<sub>DC</sub> is maximum per winding.  
 3. SRF is minimum for each winding.

*Coilcraft*

Document 142-2 Revised 7/9/97

1102 Silver Lake Road Cary, Illinois 60013 Phone 847/639-6400 Fax 847/639-1469  
 E-mail info@coilcraft.com Data by Fax 800/651-6974 Web http://www.coilcraft.com