DIP-28C-C02

28-pin ceramic DIP
(DIP-28C-C02)

Lead pitch	100 mil
Row spacing	600 mil
Sealing method	Cerdip

28-pin ceramic DIP (DIP-28C-C02) 36.83 + 1.27 (1.450 + .050) R0.64 (.025) REF 14.66^{+0.46}_{-0.18} (.577^{+.018}_{-.007}) 15.49+0.38 1.32 ± 0.25 (.052 ± .010) $(.610^{+.015}_{-.010})$ 0.81 + 0.46 - 0.30 (.032 + .018 - .012) 5.84 (.230)MAX $0.25^{\,+\,0.10}_{\,-\,0.05}$ 3.40 ± 0.36 (.134 ± .014) $(.010^{+.004}_{-.002})$ $0.46 ^{+ 0.13}_{- 0.08}$ 2.54 (.100) 2.54 ± 0.25 0.81 (.032) 15.24 (.600) 0°~15 $(.100 \pm .010)$ (.018 + .005) REF MAX TYP 33.02 (1.300) REF Dimensions in mm (inches). © 1994 FUJITSU LIMITED D28010SC-3-3

The contents of this document are subject to change without notice. Customers are advised to consult with FUJITSU sales representatives before ordering. FUJITSU is unable to assume responsibility for infringement of any patent rights or other rights of third parties arising from the use of the information or package dimensions in this document.

FIAJ code :*DIP028-G-0600-1