

TOSHIBA

Databook

Neuron® Chip
TM_PN3150/3120

2000

Echelon, LON, Neuron, LonWorks, LonTalk, LonBuilder, LonManager, LonUsers, and LonBulider are registered trademarks of Echelon Corporation.

LonLink, NodeBuilder, LonMaker, LonSupport, and LonMark are trademarks of Echelon Corporation.

The information contained herein is subject to change without notice.

The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringement of patents of other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.

Neuron[®] Chips are manufactured and sold under license from Echelon. In order to purchase Neuron Chips, customers must first enter into a Developer's License Agreement or an OEM License Agreement.

These TOSHIBA products are intended for usage in general electronic equipment (office equipment, communication equipment, measuring equipment, domestic electrification, etc.). Please make sure that you consult with us before you use these TOSHIBA products in equipment which requires high quality and/or reliability, or in equipment which could have major impact to the welfare of human life (atomic energy control, airplane, spaceship, traffic signal, combustion control, all types of safety devices, etc.). TOSHIBA cannot accept liability for any damage which may occur in case these TOSHIBA products were used in the such equipment without prior consultation with TOSHIBA.

TMPN3150 and TMPN3120 are licensed products under the patent license agreement between TOSHIBA and Bull CP8, and is prohibited from any "PORTABLE DEVICE" application as explained below:

"PORTABLE DEVICE" shall mean any portable device

- (i) complying with ISO standard 7816 width and length dimensions, plus or minus ten (10) millimeters, and with a thickness equal to or less than three (3) millimeters, or
- (ii) Incorporating an object complying with the electrical contact assignments and pattern defined in ISO standard 7816, part2, or
- (iii) with means for establishing connection (with or without contact), the purpose of which is identification of the bearer there of and /or the portable device itself, as well as storage of information and /or history relating to said bearer and /or said portable device, provided the portable device referred to in this (iii) is of pocket size.

This data book is intended for use with the following Toshiba products:

TM_PN3120B1AM, TM_PN3120E1M, TM_PN3120B1AM, TM_PN3120E1M, TM_PN3120FE3M/U, TM_PN3120A20U/M and TM_PN3120FE5 are hereinafter called TM_PN3120xx, TM_PN3150B1AF. Older versions of these parts, including the TM_PN3120AM and TM_PN3150AF, are not discussed in this book. For information on these first generation parts, contact Toshiba Corporation.

Contents

[1] Discontinued Products and Product List	19
1.1 List of Discontinued Products	21
1.2 Product Comparison	21
1.3 Comparison between Neuron Chip and Firmware Versions	21
[2] Handling Precautions	23
1. Using Toshiba Semiconductors Safely	25
2. Safety Precautions	26
2. 1 General Precautions Regarding Semiconductor Devices	27
3. General Safety Precautions and Usage, Considerations	28
3.1 From Incoming to Shipping	28
3.2 Storage	31
3.3 Design	33
3.4 Inspection, Testing and Evaluation,	37
3.5 Mounting	38
3.6 Protecting Devices in the Field	43
3.7 Disposal of Devices and Packing Materials	44
4. Precautions and Usage considerations Specific to Microcontrollers	45
4. 1 Design	45
[3] Introduction	47
3.1 General Description	49

[4]	Technical Datasheets	51
	TMPN3150B1AF	53
	TMPN3120B1AM	61
	TMPN3120E1M	68
	TMPN3120A20M / U	75
	TMPN3120FE3M / U	85
	TMPN3120FE5M	95
[5]	LonWorks® Architectural Overview	105
[6]	CPUs	109
[7]	Memory	117
7.1	EEPROM	119
7.2	R A M	120
7.3	ROM	120
7.4	External Memory	121
[8]	LonTalk Protocol	123
8.1	Multiple Media Support	125
8.2	Support for Multiple Communication Channels	126
8.3	Communication Rates	126
8.4	LonTalk Addressing Limits	127
8.5	Message Services	128
8.6	Authentication	129

8.7	Priority	129
8.8	Collision	129
8.9	Collision Detection	130
8.10	Data Interpretation.	130
8.11	Network Management and Diagnostic Services	130
[9]	Network Communication Port	131
9.1	Single-Ended Mode	135
9.2	Differential Mode	140
9.3	Special-Purpose Mode	141
[10]	Programming Model	145
10.1	Timers	147
10.2	Network Variables	148
10.3	Network Variable Aliases	152
10.4	Explicit Messages	153
10.5	Schedule	158
10.6	Additional Functions	160
10.7	Built-In Variables	166
10.8	TM3120xx Chip Firmware Extensions	166
[11]	Application I / O	167
11.1	I / O Timing Issues	175
11.1.1	Scheduler-Related I / O Timing Information	175
11.1.2	Synchronization	177
11.1.3	Firmware and Hardware Related I / O Timing Information	178
11.2	I/O Objects	179
11.2.1	Bit Input	179
11.2.2	Bit Output	180
11.2.3	Bitshift Input	181

11.2.4 Bitshift Output	182
11.2.5 Byte Input	184
11.2.6 Byte Output	185
11.2.7 Dualslope Input	186
11.2.8 Edgedivide Output	188
11.2.9 Edgelog Input	190
11.2.10 Frequency Output	192
11.2.11 I ² C I/O	193
11.2.12 Infrared Input	196
11.2.13 Leveldetect Input	197
11.2.14 Magcard Input	198
11.2.15 Magtrack 1 Input	200
11.2.16 Muxbus I/O	202
11.2.17 Neurowire I/O	204
11.2.18 Nibble Input	209
11.2.19 Nibble Output	210
11.2.20 Oneshot Output	211
11.2.21 Ontime Input	212
11.2.22 Parallel I/O	214
11.2.23 Period input	220
11.2.24 Pulsecount Input	221
11.2.25 Pulsecount Output	222
11.2.26 Pulsewidth Output	223
11.2.27 Quadrature Input	224
11.2.28 Serial Input	226
11.2.29 Serial. Output	228
11.2.30 Totalcount Input	230
11.2.31 Touch I/O	231
11.2.32 Triac Output	234
11.2.33 Triggeredcount Output	237
11.2.34 Wiegand Input	238
11.2.35 16-bit $\Delta\Sigma$ -type AD Converter	241
11.3 Notes	243

[12] Additional Functions	245
12.1 Service Pin	247
12.2 Sleep /Wake-Up Circuitry	248
12.3 Watchdog Timer	249
12.4 Reset Circuit	250
12.5 Programmable Low Voltage Detection	254
12.6 Reset Processes and Timing	255
12.6 Clocking System	262
[13] Package Types and Dimensions	265
13.1 PCB Neuron Chip Pad Layout	271
13.2 Socket Information	272
[14] Electrical Characteristics	273
14.1 Communications Port Differential Receiver Electrical Characteristics	275
14.2 Memory Interface Timing Specifications	277
Appendix A:	A-1
Neuron Chip Data Structures	A-3
The System Image	A-3
The Application Image	A-4
The Network Image	A-5
On-Chip EEPROM Layout	A-6
RAM Layout	A-7
A.1 Fixed Read-Only Data Structure	A-9
A.1.1 Read-Only Structures Field Descriptions	A-11
A.2 The Domain Table	A-15
A.2.1 Domain Table Field Descriptions	A-16

A.3 The Address Table	A-17
A.3.1 Declaration of Group Address	
Format	A-18
A.3.2 Group Address Field Descriptions	A-19
A.3.3 Declaration of Subnet /'Node Address	
Format	A-20
A.3.4 Subnet / Node Address Field	
DescriptionsA-20
A.3.5 Declaration of Broadcast Address	
FormatA-20
A.3.6 Broadcast Address Field	
DescriptionsA-21
A.3.7 Declaration of Turnaround Address	
FormatA-21
A.3.8 Turnaround Address Field	
Descriptions,A-22
A.3.9 Declaration of Neuron ID Address	
FormatA-22
A.3.10 Neuron ID Address Field	
DescriptionsA-22
A.3.11 Timer Field DescriptionsA-23
A.4 Network Variable Tables	A-25
A.4.1 Network Variable Configuration Table	
Field DescriptionsA-28
A.4.2 Network Variable Alias Table Field	
DescriptionA-29
A.4.3 Network Variable Fixed Table	
Field DescriptionsA-29
A.5 The Standard Network Variable Type (SNVT)	
Structures,A-30
A.5.1 SNVT Structure Field Descriptions ..	.A-33
A.5.2 SNVT Descriptor Table Field	
DescriptionsA-34
A.5.3 SNVT Table Extension Records ..	.A-35
A.5.4 SNVT Alias Field DescriptionsA-36

A.6 The Configuration Structure	A-37
A.6.1 Configuration Structure Field Descriptions	8
A.6.2 Direct Mode Transceiver Parameters Field Descriptions	A-42

Network Management and Diagnostic Services	B-3
Sending Network Management or Diagnostic Messages	B-6
Addressing	B-6
Configuration Changes	B-7
B.I Network Management Messages	B-8
B.1.1~ Node Identification Messages	B-8
B.1.2 Domain Table Messages	B-10
B.1.3 Address Table Messages	B-12
B.1.4 Network Variable-Related Messages ..	B-15
B.1.5 Memory-Related Messages	B-19
B.1.6 Special Messages	B-25
B.1.7 Wink	B-27
B.2 Network Diagnostic Messages	B-28
8.3 Network Variable Messages	B-34

Appendix C: C-1

C.1	AD Converter Software Driver	C-3
C.2	Programmable Reset Time	C-6

Usage Guidelines for Echelon Trademarks

Note: These guidelines do not cover usage of the LonWorks® Independent Developer Logo, the trademark LonMark®, the LonMark Logo, the Echelon® Authorized Network Integrator Logo or the Echelon® LonWorks® Integrator Partner Logo. See Section 8 below.

1. ALWAYS USE ECHELON TRADEMARKS IN AN APPROVED FORM.

Trademarks should be presented in the recommended styles shown below (all caps, upper and lower case, or a combination of large and small caps):

Registered Trademarks

Echelon®	Neuron®
LON®	LonManager®
LonTalk®	3150®
LonBuilder®	LonWorks®
LonUsers®	3120®
NodeBuilder®	LonPoint®
Digital Home®	

Other Trademarks

LonLink™	LONews™
LonSupport™	LonMaker™
LonResponse™	i.LON™

Changes or alterations in the names above are not generally 'allowed. Any variation must be cleared through Echelon's Advertising and Creative Services Director.

RIGHT

LonWorks®

RIGHT

LonTalk®

WRONG

Lonworks®

WRONG

LONTALK®

2. **ALWAYS USE ECHELON TRADEMARKS IN A MANNER CLEARLY INDICATING THAT THEY ARE TRADEMARKS OWNED BY ECHELON.**

Trademarks should be properly marked to give notice that they are, in fact, trademarks of Echelon Corporation. Registered trademarks should always be used with the federal registration symbol “®”, while marks that have not been registered (including marks that are the subject of “pending” applications) should be used with the symbol “™” where the mark initially appears. Use of the registration symbol or “™” must appear with the first usage of the trademark in a document; subsequent occurrences do not require the symbols. When used in a printed document, the symbols should be half the point size of the word and then superscripted half the point size of the word.

A footnote reference to ownership of the trademarks must be used on all products, documentation and advertisements in the following format: “Echelon, LON, LonWorks, LonBuilder, NodeBuilder, LonManager, LonTalk, LonUsers, LonPoint, Neuron, 3120, 3150, the Echelon logo, and the LonUsers logo are trademarks of Echelon Corporation registered in the United States and other countries. LonLink, LonResponse, LonSupport, and LonMaker are trademarks of Echelon Corporation.” Where appropriate, a subset of this attribution may be used.

The list of registered and unregistered marks will be updated periodically as pending applications mature to registration, and as such, it is important to determine status of the marks before using either symbol.

Trademarks should not be joined with other terms (by a hyphen, for instance) nor used with unapproved logos, graphics, photos, slogans, numbers, design features or symbols. Trademarks should never be “made plural,” never be mixed with other trademarks, and a trademark’s spelling should never be altered.

3. **ALWAYS USE ECHELON TRADEMARKS AS ADJECTIVES, NEVER NOUNS, AND THE MARKS SHOULD BE FOLLOWED BY THE APPROPRIATE GENERIC TERMINOLOGY.**

Trademarks are meant to signify the brand or source of the product and should not be used in a manner which suggests that the trademark is the name of the product. Companies that allow their trademarks to be used as nouns risk losing their rights in those trademarks. Classic examples of words that began as trademarks but were lost due to misuse include “aspirin,” “escalator” and “cellophane.” Because the public came to see these terms as the product names instead of the brand names, trademark rights were forfeited.

The most common mistake is to use the trademark as a noun instead of as an adjective followed by the generic term. Examples:

RIGHT

"LonWorks® networks can control existing home systems."

WRONG

"LonWorks® can control existing home systems."

RIGHT

"The LonTalk® protocol is built into every Neuron@ chip."

WRONG

"LonTalk® is built into every Neuron@."

4. DO NOT IMPLY OR SUGGEST THAT A PRODUCT BASED ON ECHELON'S TECHNOLOGY IS AN ECHELON PRODUCT OR THAT ECHELON SPONSORS THE PRODUCT.

While Echelon understands and appreciates the customer's need to accurately describe the technology incorporated into the product as Echelon technology, the product materials and advertising cannot wrongly imply that the customer's product is an Echelon product, explicitly or implicitly. Care must be taken to clearly distinguish Echelon's products (and trademarks) from the customer's products and marks, as discussed more specifically in these guidelines. Some basic examples are:

RIGHT

"The ACME™ light switch is for use in LonWorks® networks."

WRONG

"The LonWorks® light switch is made by ACME™."

RIGHT

"The ACME™ security system incorporates Echelon Corporation's LonTalk® protocol."

WRONG

"The ACME™ LonTalk® security system incorporates the Echelon protocol."

5. NEVER USE THE TRADEMARK "LON" AS A SEPARATE WORD, EVEN IF USED AS AN ADJECTIVE.

Even though LON is a registered trademark of Echelon Corporation, it should not be used by a customer except as part of Echelon's family of marks, such as LonTalk, LonBuilder, and the like.

6. NEVER USE AN ECHELON TRADEMARK AS PART OF YOUR NAME OR TRADEMARK.

Echelon trademarks may not be used as part of another company's mark or company name. While Echelon's marks can be used in explanatory fashion (such as "for use in LonWorks® networks"), the mark. cannot be used as part of the company or product name. The only exception to this rule relates specifically to LON, where precise guidelines have been established. The mark LON may be used ONLY if it is incorporated into a composite mark in such a way that (1) the LON portion is not highlighted in any way, including by CAPITAL letters, graphics, or stylizations, and (2) that LON is not used as the beginning letters of the composite word mark, and (3) the LON portion may not be preceded by the letters I or E if the letter forms the beginning of the word.

ACCEPTABLE	UNACCEPTABLE
Avalon	AvaLON
DRESLON	DresLON
brinlon	Lonbrin
alonet	alonet
Relongate	Elongate
	llongate

Also, customers may not personify trademarks or create characters that represent the trademarks. However, the trademarks may be used in taglines in accordance with the guidelines listed above.

7. ALWAYS USE ECHELON LOGOS (WITH WORDS OR WITHOUT) PROPERLY, IN ACCORDANCE WITH THESE GUIDELINES.

Echelon's logos are company assets just like Echelon's word marks. These logos must be used in the approved format and should never be modified without prior written approval. The Echelon Logo and Echelon Symbol are approved for use on advertising of products incorporating Echelon technology, provided that the Logo or 'Symbol is not used in a way that would give the end-user or purchaser a mistaken impression that the product is an Echelon product or is sponsored or approved by Echelon. Echelon will -provide camera-ready artwork of the Echelon Logo and Symbol.



Echelon Logo



Echelon Symbol

In general, the registered trademark symbol (®) must be used with every occurrence of the logos. Also, the trademark symbol should be used in the position indicated in these examples. When Echelon symbols and logos are used, they should be included in the footnote reference to ownership of the trademarks in addition to the trademarks symbols used with the first occurrence of the symbol or logo. Depending on which words, symbols, and logos are used, all or a subset of the following may be used: "Echelon, LON, LonWorks, LonBuilder, NodeBuilder, LonManager, LonTalk, LonUsers, LonPoint, Neuron, 3120, 3150, Digital Home, the Echelon logo, and the LonUsers logo are trademarks of Echelon Corporation registered in the United States and other countries. LonLink, LonResponse, LonSupport, i.LON and LonMaker are trademarks of Echelon Corporation."

Echelon Logo and Accompanying Words

The Echelon Logo is composed of two main components: The Echelon symbol. This is the graphic element. The registered trademark symbol (®) should appear at the lower right hand corner of the symbol when used by itself such as on products. The Accompanying Word. This is the word Echelon that may at times appear beside the Symbol. This word should accompany every use of the Echelon Logo on packaging, advertising, collateral, and documentation.

Placement Requirements

A minimal amount of empty space must be left between the Echelon Logo and any other object such as type, photography, borders, edges, etc. The required area must be $1/2x$ where x = the height of the symbol when it is used by itself.

You may not combine the Logo with any other feature including, but not limited to, other logos, words, graphics, photos, slogans, numbers, design features, or symbols.

Color Treatment. The preferred color treatment for the Echelon Logo is the four color application. This treatment uses the four Echelon colors (PMS320, PMS123, PMS185, PMS402). See the Echelon letterhead to see how these colors are used.

One Color Applications. The Echelon Logo may also appear in one-color applications. Black, white or any of the four Echelon colors is preferred. However, any color that provides sufficient contrast with the background is acceptable. The Logo may be positive or reversed.

8. CERTAIN ECHELON MARKS ARE NOT AVAILABLE FOR USE EXCEPT BY WRITTEN LICENSE AGREEMENT AND COMPLIANCE WITH STANDARDS,

Echelon owns marks which may only be used by organizations that have executed written agreements and have complied with certain requirements. These marks include the LonWorks Independent Developer Logo, the trademark LonMark, LonMark Logo, the Echelon Authorized Network Integrator Logo, and Echelon LonWorks Integrator Partner Logo. This document does not give the right to use such trademarks. These marks may only be used by organizations that have written agreements. For more information please contact the responsible program manager at Echelon.