

MOTOROLA
SEMICONDUCTOR
TECHNICAL DATA


Addendum to
MC6859
Data Security Device
ADI-827-R2

In the BUS TIMING CHARACTERISTICS table found on page 3 of the MC6859 Advance Information Data Sheet (ADI-827-R2), Input Data Setup Time shows a minimum value of 165 nanoseconds. Change this value to reflect a minimum of 340 nanoseconds.

ARCHIVE DOCUMENT NOT FOR NEW DESIGN



ARCHIVE DOCUMENT - NOT FOR NEW DESIGN

Motorola reserves the right to make changes without further notice to any products herein to improve reliability, function or design. Motorola does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights nor the rights of others. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Employment Opportunity/Affirmative Action Employer.

Literature Distribution Centers:

USA: Motorola Literature Distribution; P.O. Box 20912; Phoenix, Arizona 85036.

EUROPE: Motorola Ltd.; European Literature Center; Fairfax House; 69 Buckingham Ct.; Aylesbury Bucks; HP202NF United Kingdom.

HONG KONG: Motorola Inc.; International Semiconductor Group; P.O. Box 80300; Cheung Sha Wan Post Office; Hong Kong.



MOTOROLA